



100V P-Channel Trench Power MOSFET

General Description

The SJD010P1500 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as -4.5V. This device is suitable for use as a wide variety of applications.

Features


- Low Gate Charge
- 100% UIS Tested, 100% DVDS Tested
- High Power and current handling capability
- Lead free product is acquired

Application


- PWM Applications
- Load Switch
- Power Management

Key Performance Parametes

Parameter	Value	Unit
V_{DS}	-100	V
$R_{DS(ON_TYP)}$	156	mΩ
I_D	-11	A
Q_G	42.5	nC



Schematic Diagram



TO-252(DPAK) top view



Package Marking and Ordering Information

Device/Ordering Code	Marking	Package	Reel Size	Tape width	Quantity
SJD01P1500	D01P1500	TO-252	\	\	\

Table 1. Absolute Maximum Ratings ($T_c=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Limit	Unit
V_{DS}	Drain-Source Voltage ($V_{GS}=0V$)	-100	V
V_{GS}	Gate-Source Voltage ($V_{DS}=0V$)	± 20	V
I_D	Drain Current-Continuous($T_c=25^\circ\text{C}$)	-11	A
	Drain Current-Continuous($T_c=100^\circ\text{C}$)	-6.7	A
I_{DM} (pluse)	Drain Current-Continuous@ Current-Pulsed (Note 1)	-44	A
P_D	Maximum Power Dissipation($T_c=25^\circ\text{C}$)	48	W
	Maximum Power Dissipation($T_c=100^\circ\text{C}$)	19	W
E_{AS}	Avalanche energy (Note 2)	72	mJ
T_J, T_{STG}	Operating Junction and Storage Temperature Range	-55 To 150	$^\circ\text{C}$

Table 2. Thermal Characteristic

Symbol	Parameter	Typ	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case		2.6	$^\circ\text{C/W}$



100V P-Channel Trench Power MOSFET

Table 3. Electrical Characteristics ($T_J=25^{\circ}\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
On/Off States						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V I _D =-250μA	-100			V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-100V, V _{GS} =0V T _J =25℃			-1	μA
		V _{DS} =-100V, V _{GS} =0V T _J =125℃			-100	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20V, V _{DS} =0V			±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =-250μA	-1		-2.5	V
g _{FS}	Forward Transconductance	V _{DS} =-5V, I _D =-10A		12		S
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =-10V, I _D =-3A T _J =25℃		156	195	mΩ
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =-4.5V, I _D =-3A T _J =25℃		163	216.8	mΩ
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =-50V,V _{GS} =0V, f=1.0MHz		1950		pF
C _{oss}	Output Capacitance			47		pF
C _{rss}	Reverse Transfer Capacitance			39		pF
R _g	Gate resistance	V _{GS} =0V, V _{DS} =0V, f=1.0MHz		9.1		Ω
Switching Parameters						
t _{d(on)}	Turn-on Delay Time	V _{GS} =-10V, V _{DS} =-50V, R _L =16Ω, R _{GEN} =3Ω		15		nS
t _r	Turn-on Rise Time			55		nS
t _{d(off)}	Turn-Off Delay Time			30		nS
t _f	Turn-Off Fall Time			45		nS
Q _g	Total Gate Charge	V _{GS} =-10V, V _{DS} =-50V, I _D =-3A		42.5		nC
Q _{gs}	Gate-Source Charge			6.8		nC
Q _{gd}	Gate-Drain Charge			8.5		nC
Source-Drain Diode Characteristics						
I _{SD}	Source-Drain Current (Body Diode)				-11	A
V _{SD}	Forward on Voltage (Note 3)	V _{GS} =0V, I _S =-3A			-1.2	V
t _{rr}	Reverse Recovery Time	I _F =-3A, dI/dt=100A/μs		41		ns
Q _{rr}	Reverse Recovery Charge	I _F =-3A, dI/dt=100A/μs		50		nC


Notes 1.Repetitive Rating: Pulse width limited by maximum junction temperature.

Notes 2.EAS condition: $T_J=25^{\circ}\text{C}, V_{DD}=-50V, V_G=-10V, R_g=25\Omega, L=0.5\text{mH}$.

Notes 3.Repetitive Rating: Pulse width limited by maximum junction temperature.




Typical Electrical And Thermal Characteristics (Curves)






Typical Electrical And Thermal Characteristics (Curves)





TO-252 Package Information



Symbol	Dimensions In Millimeters		
	Min.	Typ.	Max.
A	2.200	2.300	2.400
A1	0.000		0.127
b	0.640	0.690	0.740
c(电镀后)	0.460	0.520	0.580
D	6.500	6.600	6.700
D1	5.334 REF		
D2	4.826 REF		
D3	3.166 REF		
E	6.000	6.100	6.200
e	2.286 TYP		
h	0.000	0.100	0.200
L	9.900	10.100	10.300
L1	2.888 REF		
L2	1.400	1.550	1.700
L3	1.600 REF		
L4	0.600	0.800	1.000
Φ	1.100	1.200	1.300
θ	0°		8°
θ1	9° TYP		
θ2	9° TYP		



100V P-Channel Trench Power MOSFET

Attention

This product described in this document can not be used in life support devices or systems, aircraft's control systems, and other applications whose failure can be reasonably expected to result in serious physical and/or material damage, apart from that when an application agreement is signed between customer and Linde Semiconductor.

The performances and characteristics of this product in the independent testing state are displayed in this document. Linde Semiconductor can't guarantee of the performances and characteristics of this described product that mounted in the customer's products or equipments as same as that in the independent testing state. So the customer should evaluate and test devices mounted in the customer's products or equipments.

Linde Semiconductor reserves the right to improve the designs, functions and reliability of this product and modify any and all information described in this document without notice customer, apart from that when an notice agreement is signed between customer and Linde Semiconductor.

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Linde Semiconductor hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.